

Index

- != not equal to, 107**
- # comment character, 28**
- ..., 310**
- / internet folder marker, 32**
- \ local folder marker, 32**
- ~ is modelled by, 417**
- <- assignment / gets operator, 27**
 - =.** See *R code:double equals sign to produce subsets, 251*
- 2LL, 212, 213, 297, 401**
- Absolute Risk Difference (ARD), 161**
- Aggregating data**
 - example, 222, 252
- AIC, 7, 155, 190, 216, 304, 315, 383, 393, 408, 418, 434-6, 501, 516**
- Akaike information criterion (AIC) See AIC.**
- ANCOVA. See Multiple linear regression**
- ANOVA, 24, See Multiple linear regression**
 - naming the model (R Commander), 24
 - pairwise comparisons, 25
- ARD**
 - definition of, 541
- ARR**
 - definition of, 541
- BIC, 297**
- Binomial test, 105**
 - graphing the binomial distribution, 109
 - options available to calculate the p-value, 107
 - p-value explained, 107
 - p-value graphical explanation, 109
 - R code for counts, 108
- Bland-Altman plots, 179**
- Boxplot. See graphical summaries of data**
 - definition of, 531
- c() = concatenate, 28**
- Case-control studies, 451**
- Centered variables, 510**
- Chi-squared tests**
 - confidence intervals, 123
 - mosaic plot, 114
 - one way:
 - explanation, 111
 - R code(counts), 113
 - R code(raw data), 113
 - R Commander (raw data), 112
 - R Commander (counts), 113
 - table, 115
 - what to do when expected counts less than 5, 124
 - writing up the results, 120
- Clinical significance/effect**
 - definition of, 532
- Coding frames, 5**
- Cohen's d, 474**
- Collinearity. See multicollinearity**
- Concatenate text. See R code; paste() and cat()**
- Conditional logistic regression, 451**
 - data manipulation, 452
 - matched case-control studies, 451
 - model development *clogit()*, 455
 - multiple inputs, 455
 - reversing case/control values *ifelse()*, 454, 456
- Confidence interval**
 - definition of, 531
- Converting between wide/long format, 70, 453, See Repeated measures**
- Correlation, 125-137**
 - creating and saving matrices, 253
 - part (semi-partial), 370
 - obtaining – *spcor()*, 378
 - partial, 368
 - obtaining – *pcor.test()*, 378
- Correlation ellipse**
 - definition of, 533
- Cox and Snell's R squared, 402**
- Cox Proportional Hazards Regression**
 - Checking the model, 215
 - R code, 211
 - R Commander, 210
 - survival curves for each covariate level, 215
- Creating a new variable, 246 See R Commander:**
 - creating a new variable
- Creating distributions, 232**
- Data analysis process**
 - data preparation; description; model development/evaluation, 6
- data analysis, stages of, 2**
- data collection and storage, 6**
 - dummy data for practicing, 6
 - online data collection, 6
 - who; how, 6
- Datasets provided by R**
 - ais Australian athletes (DAAG package), 136
 - anorexia data set (MASS package), 19
 - listing all, 26
 - ox - oxygen saturation (MethComp package), 180
- Dataframes**
 - converting a matrix to a dataframe
 - as.data.frame()*, 254
 - creating a new column R code, 86, 246
 - dataframe\$column name format*, 44
 - definition of, 533
 - forming in R, 29
 - naming columns in R, 29
- Degrees of freedom**
 - What does df mean and why report it?, 66
 - Structural Equation Modelling, 500
- Density plot**
 - definition of, 533
 - producing in R, 47
 - producing in R Commander, 45
- Dichotomising variables**
 - definition of, 533
- E Notation, 69, 101, 128, 335**
 - definition of, 533
- Effect size, 7, 25**
 - Confidence interval. See noncentral distributions, Clinical significance
 - Correlation and relation to Cohen's d, 132
 - definition of, 533
 - Factorial ANOVA, 470-4
 - Logistic regression, 402, also see Odds ratio.
 - Mann-Whitney U, 102-3
 - Meta-analysis, 185, 195
 - McNemar's test, 226
 - p-value, relationship with, 540
 - Poisson regression, 431
 - Regression, 146-7, 387, 390
 - Sample size, relationship with, 329-32
 - t test independent samples, 65, 80, 81
 - t test paired samples, 68
 - Wilcoxon Matched Pairs, 90
- Emoticons, 2**
- Eta squared (η^2), 470**
- Exact probability, 88**
- F distribution**
 - drawing curve, 145
 - explanation, 145
- Factor, 21, also see Boxplot for plotting.**
 - changing values *ifelse()*, 454, 456
 - converting to a factor
 - R code, 30-1, 98, 106, 318, 448
 - R Commander, 98, 245, 247-8, 460
 - Converting value labels in SPSS files to factor levels, 377
 - converting to a numeric/extracting labels, 30-1, 318
 - creating using *c("x", "y")*, 232
 - creating using *rep()*, 422, 440, 452
 - creating using *factor()*, 30, 347
 - generating level *gl()*, 30
 - definition of, 533
 - observed and manipulated subtypes, 473
 - providing names for levels
 - labels()*, 30, 247
 - rownames()*, 257-8
 - removing empty levels - *droplevels()*, 190
 - reordering, 248
- Factor analysis, 477**
 - assessing appropriateness of dataset, 479
 - Bartlett Test of Sphericity, 480
 - communality, 484
 - diagram, 478
 - EFA/CFA, 477
 - extracting factors, 481
 - factor loadings, 484
 - Hofman's complexity index, 492
 - interpreting output, 484
 - Kaiser normalisation, 492
 - Kaiser-Meyer-Olkin Measure of Sampling Adequacy (MSA), 480
 - latent variable, 477
 - matrix input instead of raw data, 489
 - multicollinearity - *det()*, 481
 - obtaining factor scores, 486
 - Principal Axis Analysis, 482
 - reification problem/misplaced concreteness, 486
 - rotation – giving meaning, 485
 - strategy, 490
 - total variance explained, 484
 - uniqueness, 484
- Factorial ANOVA, 457**
 - alternative analysis processes, 459
 - balanced design, 458
 - Beeswarm and boxplots, 463
 - blocking, 459
 - confidence intervals, 464
 - crossed factors, 458
 - describing n x n, 458
 - effect size, 470
 - comparisons, 472
 - eta squared (η^2), 470
 - generalised eta squared (η_g^2), 472
 - omega squared (ω^2), 470
 - specific comparisons mes, Cohen's d, 473
 - example, 457
 - factor types observed/measured, 472
 - homogeneity of variance assumption, 462
 - interaction/profile plots, 461, 462, 465
 - main effect, 459
 - nested designs, 475
 - number of factors = 458
 - pairwise comparisons, 468
 - pairwise comparisons Dunnett's test, 468
 - post hoc tests, 467
 - R code, 466
 - R Commander, 464
 - simple main effects, 459
 - split plot, 459
 - Tukey's Honest Significant Differences, 467
 - writing up the results, 474

Files

- Exporting
 - comma field separator as `*csv - write.csv()`, 241
 - R Commander, 241
 - R code, 242
 - tab field separator as `*DAT - write.table(sep="\t")`, 241
- importing (R Commander), 235
 - cells in excel, 239
 - clipboard, 239
 - R code, 236
 - table from Word, 239
- reading
 - rda R binary data files
 - R Commander (local and web), 43, 85, 219, 221
 - R code – `load()`, 34
 - From the web – `load(url())`, 34, 193
 - Error message, 237

Fonts

- family=, 319
- seeing what is installed `demo(Hershey)`, 14
- size - `cex=%`, 319

Function(s)

- definition of, 28, 534
- arguments, 534
- how to write your own, 534

Generalised Estimating Equations (gee), 297, 325

- standard errors, 325

Generalised Eta Squared, 472**Generalised Linear Model (GLM), 427****Global environment. See working directory****Gpower, 330****Graphical summaries of data. See Bland - Altman plots**

- `beeswarm()`, 476
- Boxplots, 22, 54 for several variables. See R code, `boxplots`.
 - subgroups, 220, 463
- CI's for means, 23
- correlation plot (coloured), 138
- correlation/scatterplot matrix, 137, 377
- density plots, 27, 43, 45
- displaying standard errors, 220
- distributions, 43
- Extended Association Plot, 276
- histograms, 43, 99
- `stripchart()`, 476
- `xyplot`. See R code: `xyplot()`

Grouping variable, 38, 97**GUI preferences, 14****History file, 264**

- deleting, 265
- saving – `savehistory()`, 264

Hypothesis (null) testing approach (NHST), 7**I as is function I() = upper case i, 445****Incidence Rate Ratio (IRR)**

- definition of, 541

Inference

- definition of, 534

Intraclass correlation coefficient (ICC), 178, 315

- irr package, 176

K-M plots, 197

- plots for publication, 206
- R code, 205

Kappa, 175

- irr, 176

Krippendorff's alpha, 177**Levels of agreement, 175, See Kappa, Krippendorff & ICC**

- more than two raters, 178

Levels of measurement, 5

- Continuous, 536
- definition of, 536
- Discrete, 536
- Interval, 537

Noir to help remembering levels, 537

- Nonimal, 536
- Ordinal, 536
- Ratio, 537

Likelihood

- definition of, 535
- in logistic regression, 400

Likelihood ratio test, 401**LINE, 141****Linear Predictor (LP), 400, 427****LISREL, 495****LOESS line**

- definition of, 536

Log linear regression. See Poisson regression**Logistic regression, 399**

- Akaike information criterion (AIC), 408
- assessing a published paper, 423
- classification table, 404, 412
- confidence intervals, 409, 417
- deviance, 401
- diagnostics, 413
- drawing confidence intervals, 413
- equation explained, 399, 424
- interpreting the coefficients, 403, 405, 417
- log likelihood, 401, 410
- logistic function, 400
- logit function (log odds), 400, 401
- model chi-square, 401
- model fit, 401, 424
 - Hosmer - Lemeshow statistic, 402, 409
- multiple inputs, 416
- predicted values, 409, 412
 - `curve()`, 409
 - `predict()`, 409, 411
- pseudo R squares, 401
- Cox-Snell, 402, 410
- Nagelkerkes, 402, 410
- R code, 407
- R Commander, 406
- sample size estimation/power, 414
- seeing the iteration history – `trace=TRUE`, 400
- sensitivity/specificity, 404
- setting iteration tolerance - `epsilon=value`, 401
- strategy, 422
- tables for binary inputs – `xtabs()`, 419
- using counts/proportions instead of raw data, 421, 422
- writing up the results, 415

Logrank and Breslow Tests, 203**Mann-Whitney U, 93-104**

- writing up the results, 103

Maximum likelihood

- definition of, 535
- in logistic regression, 400

McNemar's test, 225, 451**Meta-analysis, 183**

- Adding text `sLab=`, 189
- Baujat plot, 192
- Cochran's Q, 184
- Cochrane Collaboration, 194
- forest plot, 183
- funnel plot, 188
- heterogeneity, 184
 - Accounting for, 189
- Higgins I squared, 185
- metafor package, 183
- moderators, 190
- OpenMeta[Analyst] software, 194
- Publication bias, 188
- R squared, 190
- Random effects, 184
- `rma()`, 187
- `tau (τ)`, 184
- `trimfill()`, 189
- Writing up the results, 192

Mixed effects models, 297**Model, 140****Monte Carlo simulation, 124****Mosaic plots, 114, 275**

- mosaic plots versus bar charts, 276
- shading schemes (R code), 276
- `vcd` (Visualizing Categorical Data) package, 114

Multicollinearity, 372**Multiple linear regression, 367, See Regression.**

- added variable plots, 390
- ANCOVA, 374
- ANOVA table – obtaining/interpreting, 391
- assumptions, 367
- comparing models, 382
- confidence intervals, 381, 386
- correlated errors (violation), 395
- drawing non-parallel regression lines, 388
- drawing parallel regression lines ANCOVA
 - assumption, 386
- including and testing interaction terms, 388
- LINE, 141
- multicollinearity, 372
- overall fit, 368
- parameter estimation/evaluation, 368
- predicted values, 395
- R code, 379
- R Commander, 379
- R Commander diagnostics, 392
- dummy coding/contrasts, 374-5
- relative importance of inputs- `lmg()`, 390
- sequential/hierarchical (type I sums of squares, 371
 - standardised b(beta) R code, 380
- statistical validity, 368
- stepwise procedures, 371
- strategy, 396
- theory behind it, 368
- two continuous inputs, 377
- type III sums of squares, 373, 387, 391
- variance Inflation Factors (VIF), 372, 380
- Venn diagram
 - regression slopes, 372
 - representation R^2 , 371
 - writing up the results, 396

Multiple logistic regression. See Logistic regression.**NA (meaning 'not available') = missing value, 29****Nagelkerke's R squared, 402****Negative Predictive Value, 170**

- confidence interval, 173

New statistics, the, 7**NNT**

- definition of, 541

Noncentral distributions, 333

- chi-squared distribution, 340
- chi-squared distribution CI, 340
- chi-squared distribution effect size CI, 341
- Cohen's f effect size measure, 338
- Cohen's w, 340
- correlation (rho), 339
- F distribution, 337
- F distribution CI, 339
- MBESS package, 335
- noncentrality parameter, 333
- power values using R's built in function, 335
- t distribution, 336

Normal distribution

- definition of, 537

notepad++ text editor, 14**NppToR, 267, See Rstudio****Null hypothesis significance test (NHST) approach, 7****Null hypothesis distribution, explaining p-value**

- Binomial test, 109
- Chi-squared, 116
- t test, 63-4
- when effect size=zero, see the online chapter *R and the Raspberry pi*.

Number needed to Harm (NNH), 167

- confidence interval, 167
- Number needed to treat/harm, 165**
 - confidence intervals, 166
- Numeric**
 - definition of, 537
- Object**
 - definition of, 27
- Odds**
 - against an event, 538
 - definition of, 538
 - for an event, 538
 - range compared to probability, 539
 - relationship to probability, 539
- Odds ratio, 161, 226**
 - Advice on calculating, 164
 - definition of, 539
 - writing up the results, 163
- Omega squared (ω^2), 470**
- OpenEpi, 161**
 - help files, 164
- p-value, 540, See Null hypothesis distribution**
 - asymptotic, 88
 - bootstrapped. See re-sampling
 - displaying distribution, see online chapter *R and the Raspberry pi*
 - definition of, 540
 - exact probability, 88
 - explained using *t* value, 63
- Packages**
 - afex, 473
 - DAAG, 136
 - dependencies = TRUE option, 17
 - displaying information & version sessionInfo(), 17
 - downloading and installing a zipped version, 179
 - Epi, 17
 - epibasix, 163
 - epitools, 162
 - geepack, 321
 - ggplot2. See Publication quality graphics.
 - ibeeswarm, 463
 - install.packages() - installing, 15, 17, 70, 151, 162, 176, 200, 205, 211, 280
 - installing non-CRAMS packages, 261
 - irr, 176
 - lsr, 471
 - KappaGUI, 178
 - lme4, 304
 - loading - library(package name), 17, 19
 - MESS (Miscellaneous Esoteric Statistical Scripts), 324
 - MethComp (Functions for analysis of Method Comparison studies), 179
 - multcomp, 468
 - nlme, 303, 321
 - psych, 17
 - psychometric, 17, 151
 - QuantPsyc, 156
 - reshape2, 70, 453
 - rhosp, 17
 - rpsychi, 17
 - updating - update.packages(ask=FALSE), 17
 - UsingR, 151
 - vcd, 275
 - vcd(Visualizing Categorical Data), 114
- Partial eta, 470**
- Partial omega squared, 470**
- Plot markers (pch)**
 - definition of, 540
 - markers for males and females (Venus and Mars), 540
- Poisson distribution, 427**
- Poisson regression, 427**
 - comparing models, 436, 444, 445
 - R code anova(), 438
 - R Commander, 438
- conditional poisson regression, 450
- confidence intervals, 431, 437
- deviance, 432, 435
- drawing prediction lines, 439, 440
- equidispersion assumption, 428
- growth model approach, 445
- interaction terms, 437
- negative binomial distribution *glm.nb()*, 432, 433, 434, 438
- offset, 441, 443, 446, 448
- overdispersion, 428, 431, 433, 435, 450
- quasi-likelihood approach
 - family=quasipoisson()*, 432
- R code, 432
- R Commander, 430
- resampling, 432
- sandwich estimators, 432
- Positive Predictive Value (PPV), 170**
 - confidence interval, 173
- Predictive values, 169**
- Prevalence, 173**
- Primary outcome variable, 399**
- Publication quality graphics, 345**
 - ggplot2, 345, 346
 - Deducer, 356
 - online point and click (Jeroen Ooms), 361
 - plot(), 345
 - point and click interfaces, 354
 - qplot(), 345
 - RcmdrPlugin.KMggplot2, 351
 - layers, 345
 - aes(), 345
 - geoms(), 345, 357, 358
- R**
 - window description:
 - Data editor window, 14
 - Graphics window, 14
 - R Console window, 13
 - Script editor window, 243
- R code**
 - abline() to add a straight line to plots, 109
 - aggregate(), 252
 - as.data.frame(), 254
 - as.factor() converting a numeric variable to a factor, 98
 - attach() - sets 'current' data set, 211
 - definition of, 531
 - with(), using instead of, 48, 68, 246, 407, 428, 531
 - BA.plot(), 180
 - binom.test(), 108
 - boxplots for several variables, 87
 - cat(), 410
 - chisq.test(), 119
 - CI.RsqIml(), 151
 - clogit(), 455
 - cohen.kappa(), 176
 - col=colour, 103, 109, 205, 542
 - Confint(), 155
 - cor(), 136
 - use="complete.obs", 254
 - corr.test(), 302
 - coxph(), 211
 - cumsum() to provide cumulative frequency, 57
 - dimnames(), 119, 162
 - dotplot(), 307
 - double equals sign ==, 103
 - editing R Commander code, 254
 - epitab(), 162
 - expand.table(), 257
 - expandTable, 257
 - file=file.choose(), 255
 - font.main=number, 207
 - geeglm(), 325
 - ifelse(), 456
 - kappa2(), 176
 - kripp.alpha(), 177
 - legend(), 205
 - length() to find number of observations, 57, 280
 - levneTest(), 79
 - lm() linear Model, 155
 - lm.beta(), 156
 - lty(linetype), 205, 207
 - definition of, 536
 - lwd=line width, 109, 207
 - definition of, 536
 - main(title) chart title, 71, 87
 - Mathematical operators, 251
 - matrix(), 119, 162, 275
 - mean(), 80
 - melt(), 70
 - merge() - to join dataframes, 317
 - mosaic(), 276
 - names() to name columns of a dataframe, 318
 - ncol= number of columns, 119, 275
 - nrow= number of rows, 257
 - order, 70
 - paste() to concatenate text, 89, 104, 188, 189, 310, 319
 - pch= plot symbol number, 540
 - prop.test(), 108
 - reading files
 - rda R binary data files, 219, 241
 - rda R binary data files advantages over txt files, 221
 - read.csv() comma separated text files, 236
 - read.delim() tab separated text files, 78, 236
 - read.table() all types of text files, 236
 - riskratio(), 162
 - round(number,decimal places), 136, 433, 479
 - scan(), 237
 - sd() standard deviation, 69
 - simple.lm(), 151
 - single command spanning more than one line
 - space +, 28
 - stack() to stack columns, 80
 - str() to show object structure, 317
 - Surv(), 205, 211
 - summary() - to provide summary statistics from a dataframe or model object, 28, 30, 39, 154, 163, 187-190, 206, 295, 375, 389, 408, 422, 430, 465, 513
 - survfit(), 205
 - t() transpose function, 177
 - var.test - in place of Levenes test, 78
 - with() in place of attach(), 68
 - write.matrix() to save a matrix as a file, 255
 - xlab(x axis label), 71
 - xyplot(), 71
 - xyplot() - lattice package, 308
 - ylab(y axis label), 71
- R Commander**
 - creating a new variable, 21
 - Data ->Active data set -> Save Active dataset, 241
 - Data-> Active data set-> Export active data set, 241
 - Data->Active data set->Remove cases with missing data, 221
 - Data->Active data set->Select active data set, 234, 235
 - Data->Active dataset->Aggregate variables in active data set, 222, 252
 - Data-> Active data set -> Refresh active dataset, 86
 - Data->Import data, 235
 - Data->Manage variables in active dataset -> Compute new variable, 86
 - Data->Manage variables in active dataset->convert numeric variables to factors, 98, 106, 202
 - Data->Manage variables in active dataset->Reorder factor->levels, 221
 - Data->New dataset, 231
 - Data->Survival data->Survival data definition, 201
 - Edit data set button, 20
 - Edit data set button changing a factor to a numeric type, 223
 - Editing & manipulating variables, 245
 - converting a numeric variable to a factor
 - defining bins, 248
 - deleting, 249
 - displaying factors within a dataframe, 247

- numeric to a factor with level names, 247
 - Recoding, 245
 - renaming, 249
 - reordering factor levels, 248
 - Editing and manipulating cases (rows)
 - aggregation, 252
 - copying a subset, 251
 - copying an entire dataset, 251
 - correlation matrices, 253
 - editing autogenerated R code, 254
 - equation box, 210
 - Graphs->Histogram, 99
 - Graphs->plot of means, 220
 - importing data
 - Excel, 235
 - SPSS, 235
 - textfiles, 235
 - Importing data, 235
 - installing, 15
 - Models -> Confidence intervals, 151
 - Models -> Graphs-> Basic diagnostic plots, 150
 - opening a text file from a URL, 74
 - plugins (for R Commander)
 - RcmdrPlugin.mosaic, 277
 - RcmdrPlugin.survival, 200, 210
 - Rcmdr(), 15
 - re-opening R Commander, 16
 - Statistics-> Contingency tables -> Enter and analyse two-way table, 118
 - Statistics-> Fit models-> Generalised linear model, 408, 417, 418, 430
 - Statistics-> Fit models -> Linear regression, 149, 154
 - Statistics-> Means-> Paired sample t- test, 69
 - Statistics-> Means-> Single sample t- test, 62
 - Statistics-> Nonparametric tests-> Two sample Wilcoxon test (i.e. Mann-Whitney U), 100
 - Statistics-> Summaries-> correlation matrix, 254
 - Statistics-> Summaries -> Frequency distributions, 106
 - Statistics-> Summaries-> Active data set, 20
 - Statistics-> Survival Analysis -> Compare survival functions, 204
 - Statistics -> Survival analysis -> Estimate survival function, 201, 202
 - Tools-> Load Rcmdr plug-in(s), 200
 - View data set button, 20, 105
 - window description, 15
- R Commands**
definition of, 542
- R data types**
 factor
 - converting from a factor to a numeric variable (R Commander), 223
 - gl(), 30
 - levels, 30
 - recording factor levels (R Commander), 221
 factor creating, 30
 grouping variable, 38, 97
 numbers, 30
- R software - Downloading and installing, 11**
- Random effect, 184, 297, 305, 326**
 Correlated, 315
- Ranking, 83**
- Raspberry Pi, see online chapter R and the Raspberry pi**
- Reference group, 162, 542**
- Regression, 157**
 confidence interval for R squared, 151
 confidence intervals, 151
 Confint() for confidence intervals, 155
 diagnostics, 150
 drawing confidence /prediction intervals, 151
 R code, 155
 R Commander, 149
 standardised beta (β), 156
 visualising the line of best fit, 150
 writing up the results, 156
- Relative Risk (RR)**
definition of, 542
- relationship to odds ratios, probability and risk difference, 540
- Relative Risk Reduction (RRR) 161**
definition of, 542
- Removing cases with missing values (R Commander), 221**
- Repeated Maximum Likelihood (ML) approach, 304**
- Repeated measures**
 coef(), 305
 confidence intervals, 306
 converting from wide to long format, 300
 fixef(), 305
 Gee, 297
 lattice package, 301
 level 1 variables, 298
 level 2 variables, 298
 lme4, 304
 LMM - Linear Mixed Model, 302
 melt(), 300
 model comparison Anova(), 314
 nlme package gls() function, 303
 profile plots, 301
 random intercept and slope model, 314
 ranef(), 305
 reporting correlations across repeated measures by group, 302
 single parameter/null model, 304
 working correlation / model covariance matrixes, 321, 326
 comparing, 324
 QIC, 324
 QIC() function – MESS package, 324
 working correlation / model covariance matrixes lme4 approach, 326
- xyplot()
 - panel function, 310
 - ..., 310
 - groups(), 313
 - packet.number(), 310
 - panel.abline(), 310, 311
 - panel.text(), 310, 319
 - panel.xyplot(), 310
 - paste(), 319
 - superpose, 313
 - par.strip.text, 319
- Re-sampling, 283**
 Bootstrapping explained, 289
 Bootstrapping functions, 290
 combinations, 284
 conditional null distribution, 286
 confidence intervals, 291
 Jackknife, 293
 large samples, 287
 Mann-Whitney U, 287
 memory management (computer), 294
 Monte Carlo simulation, 287
 permutation tests, 284
 permutation tests on small samples using R, 287
 plotting, 291
 random seed number, 295
 Wilcoxon matched pairs, 287
- Risk, 161**
definition of, 542
 number needed to treat/harm, 165
- Risk difference, 161**
- Rprofile.site file - changing R startup options, 542**
- Rstudio, 267**
 break point, 268
 creating packages, 270
 debugging, 267
 linking to Notepad++, 271
 step through, 269
- Sample size requirements**
 alpha - type one error, 329
 beta - type two error, 329
 cluster trials - Aberdeen University, 332
 critical value, 329
- Gpower, 330
 PASS, 332
 power (1-beta), 329
 StudySize, 332
- Sensitivity, 169**
- Specificity, 169**
- Standard deviation**
definition of, 542
- Standardised (z) scores, 128, 246, 390, See also centered variables**
- Stripchart, 104**
- Structural Equation Modelling (SEM), 493**
 AIC, 501
 background, 493
 BIC, 501
 calculating R² from correlations and path coefficients, 497
 CFI, 501
 complex example, 520
 covariances basis for it, 499
 direct, indirect and total effects, 498
 does my bum look big in this, 501
 EQS, 501
 evaluating sem research, 521
 extending sem techniques, 521
 fixed parameters, 500
 Heywood cases, 501
 identification constraint, 500
 latent variables, 494, 500, 506-7, 509, 516, 521
 Lavaan, 511
 confidence intervals, 513
 fit/modification indices, 513, 514
 modifying code, 512
 residual analysis/local fit, 515
 manifest variables, 494
 matrix representation, 495
 a matrix, 495
 C matrix, 495
 F matrix, 495
 m matrix, 495
 S matrix, 495
 model fit, 501
 OpenMx
 code example, 517
 path
 double arrow explanation, 497
 single arrow error terms, 497
 single arrow explanation, 497
 single arrow importance of direction, 497
 path diagrams, 494
 R², 497
 RAM-format path diagram, 494
 RMSEA, 502
 sample size determination, 503
 sample size, importance of, 499
 SEM
 code, 517
 debugging, 518
 modification indices, 518
 SRMR, 501
 standardised residual variance (SRV), 497, 498
 strategy, 501, 503
 why and when to use it, 499
 Ωnyx free software tool, 504
 adding data, 505
 adding double arrowed paths (covariances), 507
 adding intercepts/mean structures, 510
 adding latent variables, 506
 adding observed variables, 505
 adding single arrow paths, 507
 comparing models, 515
 comparing nested models, 516
 creating a model, 504
 downloading, 504
 fixing/freeing parameter estimation, 507
 including standardised values in diagram, 508
 linking to R, 511
 model estimation, 508
 reloading a saved model, 511
 viewing estimation history, 509

- viewing results, 509
- viewing standardised values, 508
- Summaries**
 - describe.by() - for subgroups, psych package, 39
 - gmodels CrossTable() function for SPSS like tables, 280
 - groups of values, 39
 - numeric summaries, 38
 - overview, 37
 - percentages for each category/factor level, 57
 - relative/cumulative percentages, 57
 - subgroups - tapply(), 39
 - tapply() summary value options, 39
- t test**
 - paired samples
 - effect size, 68
 - R code, 71
 - R Commander, 69
 - single sample
 - R Commander, 62
 - two independent samples, 74
- effect size, 80
- Levene's test, 76
- R code, 78
- R code for grouping variable layout, 79
- R Commander, 77
- writing up the results, 81
- Tab character, 542**
- Tables of counts**
 - expanding into flat files, 257
 - single variable, 257
 - two variables, 258
- Tatsuki Koyama. See R code: kmplot()**
- Variance, 542**
- Vector**
 - definition of, 28
- Which test? algorithm, 526-7**
- Wilcoxon Matched Pairs Statistic, 83**
 - graphing the T+ distribution, 89
 - R code, 88
- R Commander, 87
- Working correlation matrix. See Repeated measures**
- Working directory**
 - finding it - getwd(), 265
- Working environment. See Workspace**
- Workspace, 263**
 - inspecting objects - str(), 263
 - list the objects (dataframes/objects), 263, 265
 - loading (local and web) – load(), 264
 - removing a subset of objects, 265
 - removing all objects, 263, 265
 - saving - save.image(), 264
- Z scores, 128, 147, 390, 487, 488, 542**